

**LED WATTAGE CHART**

	<b>32L</b>	<b>48L</b>
<b>350 milliamps</b>	33w	51w
<b>530 milliamps</b>	54w	80w
<b>700 milliamps</b>	71w	104w
<b>1050 milliamps</b>	106w	-

Flow is a full cutoff wall scone available from 33 to 106 watts. This low profile scone "flows" nicely with any architectural project to create a bold and sleek design. It is available with title 24 options to meet the stringent criteria for energy savings. Using the best and newest LED and electronic driver technology, the Flow is a popular choice for any project where both a sleek design and new technology are needed.

The Flow is cast aluminum with die formed aluminum parts, CNC machined and tooled for precision. The optical system is full cutoff anti-glare Star Power made of proprietary 95% miro reflective material.

The Flow comes standard with a 0-10v dimming driver with a power factor of >90. Recommended for replacing up to 250 watts of HID with savings of 70% or more with virtually zero maintenance.

**BUY AMERICAN**

To ensure the latest BAA/TAA/BABA Standards are being met, please select BAA, TAA, or BABA in the options section. Please contact the factory before placing an order for any NLS products requesting BAA (Buy American Act), TAA (Trade American Act), or BABA (Build America, Buy America).



**STAR POWER™ OPTICAL SYSTEM**

The Star Power™ reflector is an excellent system which provides great value and performance. Star Power Patent number: 10168023

Project Name:

Type:

## FLW-2 ORDERING GUIDE

Cat#	Light Dist.	No. of LEDs	Milliamps	Kelvin Temp	Volts
Flow 2 (FLW-2)	Type 4 (T4)	32 (32L) 48 (48L)	350 (35) 530 (53) 700 (7) 1050 (1) ①	Amber 585-600nm (AMBER) ② 2700K, 70 CRI (27K7) 2700K, 80 CRI (27K8) ① 3000K, 70 CRI (30K7) 3000K, 80 CRI (30K8) ① 3500K, 80 CRI (35K8) ① 4000K, 70 CRI (40K7) 4000K, 80 CRI (40K8) ① 5000K, 70 CRI (50K7) 5000K, 80 CRI (50K8) ①	120-277 (UNV)
Mounting	Color	Control Options	Options	Lens Options	
Wall Mount (WM)	Bronze Textured (BRZ) White Textured (WHT) Smooth White Gloss (SWT) Silver Metallic (SVR) Black Textured (BLK) Smooth Black Gloss (SBK) Graphite Textured (GPH) Grey Textured (GRY) Green Textured (GRN) Hunter Green Textured (HGN) Custom (CS)	Button Photocell (PC) ③	Marine Grade Finish (MGF) Emergency Battery Back-Up 4w (EM4) Emergency Battery Back-Up 8w (EM8) Emergency Battery Back-Up 14w (EMCP) Emergency Battery Cold Pack 14w (EMCP) 20KA Surge Protector (20K) Buy American (BAA) ④ Trade American (TAA) ④ Build America Buy American (BABA) ④ Custom Controls Integration (CCI) ④	Polycarbonate Lens (PL)	

### Notes:

- ① 32L Only
- ② Consult Factory for Lead Time. Consult Factory for 90 CRI Requests
- ③ Universal Voltage 120-27
- ④ Please contact Factory for Custom Control Integration requests (nLight, NX, WaveLinX, Crestron, DMX/RDM, Synapse, Casambi, Dali II, Avi-On, or other control systems)
- ⑤ Turtle Safe
- ⑥ Consult factory for all BAA/TAA/BABA requests



701 Kingshill Place, Carson, CA 90746  
Call Us Today (310) 341-2037

[nslighting.com](http://nslighting.com)

## PRODUCT SPECIFICATIONS

### ELECTRICAL

- 120-277 Volts (UNV) or 347-480 Volts (HV)
- 0-10V dimming driver
- Driver power factor at maximum load is  $\geq .95$ , THD maximum load is 15%
- LED Drivers Ambient Temp. Min is  $-40^{\circ}\text{C}$  and Ambient Temp. Max ranges from  $50^{\circ}\text{C}$  to  $55^{\circ}\text{C}$  and, in some cases, even higher. Consult the factory for revalidation by providing the fixture catalog string before quoting and specifying it.
- All internal wiring UL certified for 600 VAC and  $105^{\circ}\text{C}$
- CRI 70, 80 or 90
- Color temperatures: Amber, 2700, 3000K, 3500K, 4000K, 5000K

### CONSTRUCTION

- Cast Aluminum. CNC Die Formed.

### OPTIONS

- MARINE GRADE FINISH (MGF) - A multi-step process creating protective finishing coat against harsh environments. Chemically washed in a 5 stage cleaning system. Pre-baked, Powder coated 3-5 mils of Zinc Rich Super Durable Polyester Primer. Oven Baked. Finished Powder Coating of Super Durable Polyester Powder Coat 3-5 mil thickness.

- POLYCARBONATE LENS (PL)
- EMERGENCY BATTERY BACK-UP (EB)
- 20KA SURGE PROTECTOR


### CONTROL OPTIONS

- PHOTOCELL
- Controls Agnostic: Please contact factory for your preferred controls option.

### OPTICS

Recessed Star Power Optical System is 95% reflective material. Utilizes a linear diffused pattern, softening the light distribution and eliminating any dark shadows or striations.

- IES Types



TYPE IV (T4)

- Controls Agnostic: Please contact factory for your preferred controls option. (nLight, NX, WaveLinx, Crestron, DMX/RDM, Synapse, Casambi, DALI II, Avi-On, or other control systems)

### FINISH

- 3-5 mils electrostatic powder coat.
- NLS Lighting standard high-quality finishes prevent corrosion and protects against extreme environmental conditions

### WARRANTY

Five-year limited warranty for drivers and LEDs.

### LISTINGS

- UL Listed

### BUY AMERICAN OPTION

While all of the NLS Lighting products listed in this document qualify for the Buy America(n) Act of 1933, we reserve the right to change our listings without notice.

The information provided above is for general informational purposes only. We encourage you to consult legal professionals for advice particular to your projects concerning BAA, TAA, BABA or Buy America.

Additional NLS Products that meet BAA, TAA standards can be found at the following link:

<https://nlsighting.com/buy-american/>



The information and specifications on this document are subject to change without any notification. All values are design, nominal, or typical or prorated values when measured under internal and external laboratory conditions.



701 Kingshill Place, Carson, CA 90746  
Call Us Today (310) 341-2037

[nlsighting.com](https://nlsighting.com)

## PRODUCT SPECIFICATIONS


**FLOW - LUMEN DATA CHART**

PART NUMBER	T4 Lumens	T4 LM/W	Watts
FLW-2-32L-35-30K7	2772	84	33
FLW-2-32L-35-40K7	2871	87	33
FLW-2-32L-35-50K7	2970	90	33
FLW-2-32L-53-30K7	4536	84	54
FLW-2-32L-53-40K7	4698	87	54
FLW-2-32L-53-50K7	4860	90	54
FLW-2-32L-7-30K7	5964	84	71
FLW-2-32L-7-40K7	6177	87	71
FLW-2-32L-7-50K7	6390	90	71
FLW-2-32L-1-30K7	8904	84	106
FLW-2-32L-1-40K7	9222	87	106
FLW-2-32L-1-50K7	9540	90	106
FLW-2-48L-35-30K7	4284	84	51
FLW-2-48L-35-40K7	4488	88	51
FLW-2-48L-35-50K7	4743	93	51
FLW-2-48L-53-30K7	6720	84	80
FLW-2-48L-53-40K7	7040	88	80
FLW-2-48L-53-50K7	7440	93	80
FLW-2-48L-7-30K7	8736	84	104
FLW-2-48L-7-40K7	9152	88	104
FLW-2-48L-7-50K7	9672	93	104


**LUMEN MAINTENANCE DATA**

Ambient Temperature	Drive Current	L90 Hours*	L70 Hours**	30,000 Hours*	50,000 Hours*	60,000 Hours*	100,000 Hours**
25°C	Up to 700mA	58,000	173,000	95.7%	91.6%	89.6%	82.1%
	1050mA	38,000	96,000	93.0%	85.4%	81.8%	68.8%
*Reported extrapolations per IESNA TM-21				**Projected extrapolations per IESNA TM-21			


## LED KELVIN RANGE




**AMBER**  
585-600 nm




2700K 70 CRI




3000K 70 CRI



3500K 80 CRI



4000K 70 CRI



5000K 70 CRI

Color	Dominant or Peak Wavelength Range (nm)	
	Minimum	Maximum
Amber	585	600

## PRODUCT SPECIFICATIONS

Luminaire	A	B	C
FLW-2	11.48 in	15 in	9.27 in

