

Area, Site, and Roadway Just Got Brighter

Introducing the new NV-3

NV-3
(40,000 Lumens to 103,000 Lumens)

Specification Features

- Ideal High Lumen Output for Area, Site, Roadway, and Large Parking Venues such as: Corporate Parks, Shopping Malls, Event & Sports Stadiums, Roadways, and Airports
- Sleek Robust Design of the NV-3 (Weight: 55 lbs., EPA: 0.73) Compliments the NV-1 and NV2
- IES Distributions T2, T3, T4, and T5
- 160L, 192L, and 256L LED Configurations, 403 to 805 Watts
- 2700K, 3000K, 3500K, 4000K, 5000K CCT Multichip High Power 70 & 80 CRI LEDs
- IP66 Rated Against Dust & Water Ingress, IK10 Rated for Tamper/Vandalism/Impact Protection
- Mountings available have a 1.5G to 3G Vibration Rating: Architectural Sweep Arm, Direct Pole 6" and 11" Arm, Knuckle Mount, Wall Mount, Trunnion Mount, and Tennis Arm
- 20kA Surge Protection (120V - 480V), 0 - 10V Programmable, Dimming LED Drivers
- LED Drivers Ambient Temp. Min (°C) is -40°C and Ambient Temp. Max (°C) Ranges from 50°C to 55°C
- Silicone Micro Optics Providing 96% Clarity and Heat Resistant up to 150°C
- 9 Standard Finishes, Custom and Marine Grade Finish Available
- Controls Agnostic, Compatible with Most Control Systems and Sensors
- Environmentally Friendly Product Which Reduces Energy Consumption, L70 > 100,000 hours
- Buy America(n) Option Available, Easy to Install Mounting
- Cost Competitive and Short Shipping Lead Times in Days & Weeks

NV-1

(2,000 Lumens to 26,000 Lumens)



NV-2

(19,000 Lumens to 52,000 Lumens)



FIXTURES & POLES | BUY AMERICA(N) | QUICKSHIP FLASH

