



The New TRAC Stars

Trac Linear Signlighter

- 1,603 to 24,537 Lumen range
- Two different mounting options: Adjustable Arm and Fixed Arm,
- Five different arm lengths: 3", 6", 12", 18", and 24"

Trac Linear Ceiling Mount

- 1,603 to 24,537 Lumen range
- Ceiling Mount (All 5 Sizes)
- Optional Diffused Polycarbonate Visual Comfort Lens available for lower ceilings

Trac Linear Pendant Mount

- 1,603 to 24,537 Lumen range
- Pendant Mount (Size 4 and 5 only)
- Three different arm lengths: 12", 24", 36"

Trac Linear Wall Mount

- 1,603 to 24,537 Lumen range
- Wall Mounted up or down

Trac Linear Floodlight

- 1,603 to 24,537 Lumen range
- Knuckle Mount
- 180° Adjustable angle

One iconic shape, 5 sizes, 7 different mounting options, lighting made easy

- 1,603 to 24,537 Lumen range
- Eight distributions: 15° Very Narrow Beam, 30° Narrow Beam, 55° Medium Beam, 85° Wide Beam, Type 2, Type 3, Type 3M, Type IV Forward Throw Wide, and Type V Wide (not available for the Trac Linear Wall Mount)
- Five different fixture sizes, multiple current choices
- 0–10V programmable, dimming LED drivers with an operating range of -40°C to 50°C for use in most climates with a THD @ Max Load < 15%
- NEMA 7-Pin Receptacle, FSP with Motion Sensor options, Button Photo Cell option
- Lens Options: Clear Tempored Glass, Diffused Polycarbonate Visual Comfort, and HAL
- 20kA Surge Protection, plus Emergency Battery options
- Ten standard finishes, marine grade finish and custom finish available
- Buy America(n) option compliant