



NV WALL PACK

FORM, FUNCTION & RELIABILITY

- ✓ **Silicone Micro Optics**—Will not Yellow, Oxidize, become Brittle or Crack. IP67 Protective Light Engine Seal. Fifty percent More Heat resistant to LED temperature than common PMMArylic or Polycarbonate optics. Vandal Proof!
- ✓ **Dark Sky Compliant**—Recessed LEDs and a Full Cut Off design.
- ✓ **Energy Savings (Uniform light distribution)**—Can provide equivalent foot candles at same distance at less wattage than competitors LED wall packs.
- ✓ **Three IES Light Distributions**—T2, T3, and T4.
- ✓ **Depreciation**—Over 173,000 hours of L70 designed for long term Municipal and infrastructure Projects.



FULL CUT OFF DESIGN RECESSED OPTICS DARK SKY COMPLIANT

NV-W ASSEMBLY VIEW

HOUSING

Die Cast Aluminum.
Side and Rear Conduit Entry.

FINISH

Textured—3-5 mils powder coated. Applied electrostatically. NLS' standard high-quality finishes prevent corrosion and protect against extreme environmental conditions.

5 DEGREE INTERNAL TILT
44% measurable light increase.

MICRO OPTICS

IP67 Rated, Silicone Optic modules designed to withstand extreme weather conditions. Thermal, UV, vandal resistant. Rated up to 150° C.

**SIDE AND REAR
CONDUIT ENTRY**

FEATURES

MICRO OPTICS

IES Types T2, T3, T4

KELVIN TEMPERATURE

Amber (565nm), 2700, 3000, 3500, 4000, 5000

CRI: 70, 80

CERTIFICATIONS

UL Listed
IP65 Rated Housing
IP67 Optics
DesignLights Consortium®



OPTIONS

Surge Protector (20KA)
Marine Grade Finish (MGF)
Dimming Control with Motion Sensor | 8', 20' Hts. (DCX)
Emergency Battery Back-Up | 4w, 8w, 16w (EMX)
Emergency Cold Pack Battery (EMCP)
Housing Extension (HE)
Button Photocell (PC)
Nema 7-Pin Receptacle (PE7)
Vanity Plate 16" SQ (VP16)

*Not all product configurations may be DLC Premium or DLC qualified. Visit www.designlights.com/QLP for product listings.

NLS LIGHTING, LLC
701 Kingshill Place, Carson, CA 90746
T (310) 341.2037 | nlsighting.com