

# ORGANIX

## ORX-3 LED Parking Garage, Canopy, High Ceiling Luminaire

### ORX-3-CM Benefits

- The Organix iconic low profile design enhances any contemporary architectural standard to high ceiling Garage or Canopy setting
- 7,895 to 53,029 Lumen range with a 80L, 96L, 128L, and 144L LED configurations
- Standard Silicone Micro Optic distributions include: TE (Concentrated Entry), T3DL (Drive Lane), T4M (Type 4 Medium), and T5 (Type 5)
- New Performance Silicone Micro Optic distributions include: T4FTW (Type 4 Forward Throw Wide) and T5W (Type 5 Wide) for greater coverage
- 4 lens options available: No Lens, Clear Tempered Glass Lens Diffused Polycarbonate Visual Comfort Lens, and HAL Lens
- Amber, 2700K, 3000K, 3500K, 4000K, and 5000K CCT Multichip High Power 70 or 80 CRI standard
- For additional glare control there is the Glare Shield and House Side Shield options

Up to 53,029 Lumens

- Ceiling Mount or Pendant Mount standard
- 20kA Surge Protection (120V - 480V), 0-10V programmable, dimming LED drivers with an operating range of -40°C to 50°C for use in most climates with a THD @ Max Load < 15%
- Bird Spikes and Bird Shroud options are available
- 10 standard finishes, marine grade finish and custom finish available
- Controls Agnostic: compatible with most control systems and sensors
- Die-Cast Aluminum Housing for a precision fit, greater heat dispersion, and durability
- Environmentally friendly product which reduces energy consumption, L70 > 140,000 hours
- Buy America(n) option compliant

FIXTURES & POLES | BUY AMERICA(N) | QUICKSHIP FLASH



AREA, SITE  
& ROADWAY



ARCHITECTURAL  
& DECORATIVE  
POST TOP



BOLLARDS  
& COLUMNS



FLOODLIGHTS



WALL MOUNT



GARAGE, CANOPY  
& CEILING



TENNIS &  
PICKLEBALL



POLES  
& BASES



ARMS



ACCESSORIES