

ORX-3-PB Benefits

- The Organix family's sleek and low profile can carry any establishment's esthetic from the parking lot to the pickleball court
- 21,460 to 59,064 Lumen range with a 144 LED configuration and up to 157 Lumens Per Watts
- Standard Silicone Micro Optic distributions include 15 (15° Very Narrow Beam), 30 (30° Narrow Beam), 55 (55° Medium Beam), and 85 (85° Medium Beam)
- New Performance Silicone Micro Optic distributions include: T5W (Type 5 Wide) for greater coverage
- 3 lens options available: No Lens, Clear Tempered Glass Lens, and Diffused Polycarbonate Visual Comfort Lens
- 3000K, 3500K, 4000K, and 5000K CCT Multichip High Power 70 or 80 CRI standard
- For additional glare control there is the Glare Shield and House Side Shield options

- Pendant Mount standard
- 20kA Surge Protection (120V 480V), 0−10V programmable, dimming LED drivers with an operating range of -40°C to 50°C for use in most climates with a THD @ Max Load < 15%
- Bird Spikes and Bird Shroud options are available
- 10 standard finishes, marine grade finish and custom finish available
- Controls Agnostic: compatible with most control systems and sensors
- Die-Cast Aluminum Housing for a precision fit, greater heat dispersion, and durability
- Environmentally friendly product which reduces energy consumption, L70 > 140,000 hours
- · Buy America(n) option compliant





FIXTURES & POLES | BUY AMERICA(N) | QUICKSHIP FLASH





















