

TRAC BOLLARD (TBA) ANGLED RECTILINEAR BOLLARD

TRAC

FORM - FUNCTION - RELIABILITY

- · Elegant Rectilinear Extruded Aluminum Housing
- Silicone Micro Optics
- IES Distributions T2, T3, T4
- L70 173,000 Hours
- 0-10V Dimming Drivers
- 2700, 3000, 3500, 4000, or 5000 Kelvin
- 700-6,400 Lumens, 10-56 Watts
- Advanced Thermal Management System
- 5 mils Electrostatic Powder Coat
- IP67 Light Engine







IP67 Rated, Silicone Optic modules designed to withstand extreme weather and thermal conditions, UV, vandal resistant. Rated up to 150° C

HOUSINGExtruded aluminum

SPECIFICATION FEATURES

- Silicone Micro Optics Will not Yellow, Oxidize, become Brittle or Crack. IP67 Protective Light Engine Seal. Fifty Percent More Heat resistant to LED temperature than common PMMA Acrylic or Polycarbonate optics. Vandal Proof!
- **Lighting Solution** The TRAC Collection has an L70 of 173,000 Hours. It utilizes the best electrical components available including 0-10V Dimming Driver(s), and a robust Thermal Management System
- Extruded, Fabricated, Powder Coated and Assembled in the U.S.A.

